


e-medical™ AIO 724-IP65

Powerful All-in-One PC for
medical environments






IP65
Splash-proof

Full IP65 protection.

In operating theatres, emergency rooms, clean rooms and laboratories, computer systems are subject to particularly high requirements with regard to their technical and hygienic properties. Our **e-medical™ All-in-One computers** meet the high requirements for medical electrical devices according to the European standards 60601-1 and 60601-1-2. The fanless computers are quiet, slim and modern panel computers, which especially convince with a full IP65 housing. Optionally, the 24 inch glass panel is also available with touch and combines computer, monitor, keyboard and mouse in one device.

Benefits:

- › **IP65 – completely splash-proof**
- › **Space-saving due to full-flat design**
- › **Also available with touch function**
- › **Dual LAN connectors**
- › **Integrated WLAN**
- › **Antibacterial housing**
- › **According to EN 60601-1 / EN 60601-1-2**
- › **only 7.8 kg weight**



Optional with Touch

Technical Data

Technical Data

General information

e-medical™ AIO 724-IP65

Processor	Intel® Core™ i5 7200U 3 MB Cache, bis zu 3.1GHz Intel® Core™ i7 7600U 4 MB Cache, bis zu 3.9GHz
RAM	8 GB (32 GB max.)
Hard drives	500 GB SSD, Intel SATA RAID 0/1 supported
Compatibles OS	Windows® 10 (not included)
Thin Client Compatibility	Citrix, Microsoft, VMware
Interfaces	2x USB2.0, 4x USB 3.0, 1x Seriell, 1x HDMI, 1x DP, 2x LAN (Isolation optional), PCI-e
Security	RFID (intern, optional), TPM Support
WLAN	802.11 ac (internal)
Supply voltage	12V DC
Power consumption	29 W
Weight	7.8 kg
Dimensions (WHD)	557 x 355 x 40 mm
IP protection class	IP65 Full surface
Case	Front: Full flat Design Rear: antibacterial, closed, fanless, white
Operating temperature	0 °C up to 40 °C
Storage temperature	-20 °C up to +60 °C
Standards	CE, FCC-B, RoHS, IEC 60601-1, IEC 60601-1-2, Class 2 double insulation, Energy Star
Optional	Touch: Capacitive 10 finger Multi Touch, Webcam 2 MP, internal smart card, internal RFID

Display

Type	24" TFT LED
Active screen area	521.28 (H) x 293.22 (V)
Resolution	1920 x 1080 (Full HD)
Pixelpitch	0.2715 x 0.2715 mm
Contrast	1000:1 typical
Brightness	300 cd/m ²
Response time	5 ms
Item No.	2012138

Accessories

